

W773-W80

GPU Workstation - Intel® Xeon® W-3500/2500/3400/2400



Key Features

- Supports up to 4 x Dual slot Gen5 GPUs
- Single Intel® Xeon® W-3500/3400 Processors
- Single Intel® Xeon® W-2500/2400 Processors*
- 8-Channel DDR5 RDIMM, 8 x DIMMs
- Intel® W790 Chipset
- 2 x 10Gb/s LAN ports via Intel® X710-AT2
- 2 x M.2 slots with PCIe Gen4 x4 interface
- Up to 8 x 3.5"/2.5" SATA bays
- 5 x PCIe Gen5 x16 slots
- 2 x PCIe Gen4 x16 slots
- Single 2000W ATX 80 PLUS Gold power supply

Specification

Dimensions	Pedestal (W218 x H455 x D726.3 mm)
Motherboard	MW83-RP0
CPU	Intel® Xeon® W-3500 Processors Intel® Xeon® W-2500 Processors ^[1] Intel® Xeon® W-3400 Processors Intel® Xeon® W-2400 Processors ^[1] Single processor, TDP up to 385W ^[1] Carriers for Intel® Xeon® W-2500/2400 Processors are not included. *Please select Intel® Xeon® W-3500/3400 Processors to enable all functions.
Socket	1 x LGA 4677
Chipset	Intel® W790
Memory	8-Channel DDR5 RDIMM, 8 x DIMMs Up to 4800 MT/s *Only 4 x DIMM slots are supported with Intel® Xeon® W-2500/2400 Processors.
LAN	2 x 10Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mbps Management LAN
Video	Integrated in ASPEED® AST2600 - 1 x VGA port
Audio	Realtek® ALC897 HD Audio Codec Supports 2/4/5.1/7.1 channel configurations Rear: 3 x Audio jacks (Audio in/Audio out/Mic) Front: 2 x Audio jacks (Audio out/Mic)
Storage	Front hot-swap: 4 x 3.5"/2.5" SATA 4 x 3.5"/2.5" SATA (optional) Internal M.2: 2 x M.2 (2280), PCIe Gen4 x4 *Storage card is required to support NVMe and SAS drives.
RAID	Intel® SATA RAID 0/1/10/5

Peripheral Drives	5.25" space reserved for ODD device
PCIe Expansion Slots	5 x PCIe Gen5 x16 ^[1] 2 x PCIe Gen4 x16 ^[1] Slot_4/5/6 are not supported with Intel® Xeon® W-2500/2400 Processors. *The system supports the following GPU configurations: - Dual-slot 300W GPUs: 4 x GPUs - Dual-slot 600W GPUs: 1 x GPU - Triple-slot GPUs: 2 x GPUs
I/O Ports	Front: 2 x USB 3.2 Gen1 Rear: 1 x USB 3.2 Gen2x2, 3 x USB 3.2 Gen2x1, 1 x VGA, 2 x RJ45, 1 x MLAN
TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Power Supply	Single 2000W ATX 80 PLUS Gold power supply AC Input: 100-240V *The system power supply requires C19 power cord.
System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
System Fans	Middle: 3 x 120x120x38mm Rear: 1 x 120x120x25mm
Operating Properties	Operating: 10°C to 30°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Packaging Content	1 x W773-W80 1 x CPU fansink 1 x W-3500/3400 (E1A) carrier ^[1] ^[1] Carriers for Intel® Xeon® W-2500/2400 Processors are not included.
Ordering Part Numbers	6NW773W80MR-000-3*
Optional Parts	- W-2500/2400 (E1B) carrier: 12KRC-014677-12R - Rail kit for W7x3 series ((A)+(B)+(C)+(D)): (A) 25HB2-A66126-K0R (Slide Rail), Q'ty: 1 set (B) 25HB4-W77304-C0R (Rack Ear Right), Q'ty: 1 set (C) 25HB4-W77305-C0R (Rack Ear Left), Q'ty: 1 set (D) 25HB7-W77300-C0R (Top Cover for Assembly), Q'ty: 1 set



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

