

AXP1440 & Centellis® 4440

Bladed Server Platform

DATA SHEET

The AXP1440 and Centellis® 4440 40G ATCA systems are specifically designed to address the unique requirements of defense and networking applications

- Architected for high availability applications
- PICMG 3.7 Release 1.0 compliant thermal performance
- Up to 350W per blade power distribution
- Redundant shelf management and alarms
- 12 payload & 2 switching slots with rear transition module capability for each slot
- PICMG 3.0 ATCA mechanical formfactor and power/cooling design
- PICMG 3.1 ATCA high performance switch fabric capable of 1, 10, and 40Gbps operation

Advanced TCA®

DESIGNED & ASSEMBLED IN
USA

The SMART Embedded Computing AXP1440 is a rugged high-availability ATCA® chassis with a rich ecosystem of blades and software suited to defense, security and networking applications. The chassis is available configured with redundant 40G switch blades as the Centellis® 4440

BENEFITS

- Bladed architecture for scalability, minimized cabling and ease of maintenance
- Application-ready configurations shorten time-to-market
- Strong ecosystem of off-the-shelf or custom blades allows the platform to be easily configured for a range of applications & upgraded as new technologies become available



 **SMART™**
Embedded Computing



Rich Content Ecosystem

- Intel Xeon-based server blades with storage options
- High throughput packet processing blades based on Cavium Octeon or Intel Architecture processors
- 40G switching blades with system control functionality

Enclosure

- 14 blade slots each with rear transition module (RTM) slots
 - 2 switch/system manager slots
 - 12 8U payload slots for application blades
- 40/10/1G-capable backplane delivering up to 80G fabric bandwidth to each slot
- Dual shelf managers and alarm modules
- Front Alarm Display Panel (ADP)
 - Two COM ports (one for each shelf manager)
 - Telco alarm indicators (PWR, Minor, Major, Critical)
 - Alarm reset
 - Telco Alarm interface (dry relay contact, DB-15)
- Front-to-rear cooling
 - Redundant fan trays – one bottom fan tray, one top fan tray
- PICMG 3.7 Release 1.0 compliant thermal performance
- Cable Management System
- Enclosure Dimensions & Weight
 - 573 mm high x 449 mm wide (not including mounting ears) x 544 mm deep
 - Weight: 39.7 kg / 87.5 Lbs.
- Operating Environment
 - Operating temperature range (DC): -5°C to 55°C @ 90% non-condensing humidity
 - Storage temperature range: -40°C to 70°C @ 95% non-condensing humidity

Fabric Switch

Centellis 4440 includes redundant 40G Ethernet ATCA-F140 switch blades providing the communications fabric. The switch blades also include OPTIONAL system management functionality.

- ATCA 1G, 10G, 40G fabric switch interface in dual star topology
- Integrated Linux-based software package for system & switch management
- Customization options with AMC site, disk bay and telecom clocking function
- Face plate interfaces
 - Service processor interface via 1G Ethernet (RJ-45) and RS-232 serial
 - Base interface via 1G/10G Ethernet (SFP+) ports
 - Fabric interface via 1G/10G and 40G Ethernet ports (SFP+ and QSFP+)
 - Optional Telecom Clock interfaces
- Blade Services Software
 - Linux OS
 - Firmware Upgrade Facility
 - Hardware Platform Interface (HPI) to manage platform elements configured for multi-shelf management support
 - SRstackware® switching software including switch chip initialization, configuration, management as well as a full suite of L2 and L3 protocols





The SMART Embedded Computing Experience

SMART EC has over 30 years of experience serving the defense and telecommunications industries and has hundreds of thousands of products deployed in the world's communications networks and defense systems. With that long experience comes a deep understanding of our customers' requirements for on-time, consistent and high quality product coupled with excellent customer support. We deliver on all counts from our own world-class factory and seasoned support experts.

We're very flexible and agile. We recognize that you may need your system to have your own unique branding. No problem. We're used to that. We have services that allow you to define the look and feel that's consistent with your company's branding and aesthetic standards. Our flexibility isn't just limited to look and feel. Integration services, unique support requirements, longevity of supply, drop shipments and many more services are designed to make it easy to do business with us and quick for you to get to market and deploy smoothly.

Regulatory Compliance

Item	Description
Designed to comply with NEBS	GR-63-CORE, NEBS Physical Protection, Level 3
	GR-1089-CORE, Electromagnetic Compatibility and Electrical Safety – Generic Criteria for Network Telecommunications Equipment. Level 3, Equipment Type 2
Designed to comply with ETSI	ETSI Storage, ETS 300 019-2-1, Class 1.2 equipment, Not Temperature Controlled Storage Locations
	ETSI Transportation, ETS 300 019-2-2, Class 2.3 equipment, Public Transportation
	ETS 300-132-2 Environmental Engineering (EE); Power supply interface at the input to telecommunications equipment; Part 2: Operated by direct current (dc)
	ETSI Operation, ETS 300 019-2-3, Class 3.1 equipment, Partly Temperature Controlled Locations
Designed to comply with Acoustic	ETS-300-753, Equipment Engineering (EE); Acoustic noise emitted by telecommunications equipment
EMC	EN-300-386 Electromagnetic compatibility and Radio spectrum Matters (ERM); telecommunication network equipment; ElectroMagnetic Compatibility (EMC) requirements, Telecommunication equipment room (attended)
	FCC 47 CFR Part 15 Subpart B (US), Class A
	EMC Directive 89/336/EEC (EU)
	AS/NZS 3548 (Australia/New Zealand), Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment
	VCCI Class A (Japan), Voluntary Control Council for Interference by Information Technology Equipment
	Industry Canada ICES-003 Class A
Safety	Compliance to UL/CSA 60950-1, EN 60950-1 and IEC 60950-1 CB Scheme. Marked with U.S. NRTL, Canadian Safety and CE Mark.
RoHS/WEEE compliance	Directives 2011/65/EU / 2015/863 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on the restriction of the use of certain hazardous substances in electrical and electronic equipment. (RoHS)
	DIRECTIVE 2002/96/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on waste electrical and electronic equipment (WEEE)





Ordering Information

Part Number	Description
AXP1440	ATCA SHELF - 14 SLOT, 19", 13U, 40G, PP SHMM
Optional Platform Products	
RTM-ATCA-F140	RTM for the ATCA-F140 with SFP/SFP+/QSFP sockets
PRAMC-7311-16GB	Mid-size AMC with Intel Core i7-2655LE processor, 2.2GHZ, 16GB DDR3
SFP-CO-RJ-45	1G Small Form-factor Pluggable (SFP) - copper - RJ-45 connector
SFP-MM-SX-LC	1G Small Form-factor Pluggable (SFP) module - 850NM, SX, LC connector
SFPP-MM-SR-LC	10G Small Form-factor Pluggable Plus (SFPP) module - 850NM, SR, LC connector
SFPP-SM-LR-LC	10G Small Form-factor Pluggable Plus (SFPP) module - 1310NM, LR, LC connector
SFPP-MM-SR-LC-DR	10G Small Form-factor Pluggable Plus (SFPP) module - dual rate, 850NM, SR, LC connector
SFPP-CO-RJ-45-3M	10G Small Form-factor Pluggable Plus (SFPP) Direct Attached Copper (DAC) cable - 3 meters
CABLE-OPT-F102-5M	Optical cable for multi-mode, SFP and SFPP connections (5M)
QSFP-40G-SR4-MODULE	40G QSFP+ MODULE - 40GBASE-SR4 - 850NM - FOR MULTIMODE FIBER - MTP (MPO) CONNECTOR
CABLE-COP-QSFP-3M	40G QSFP+ Direct Attached Copper (DAC) cable - 3 meters
CABLE-OPT-QSFP-5M	Optical cable for multimode, QSFP+ connections, 2x MTP (MPO) connectors - 5 meters
CABLE-B-OPT-QSFP-5M	Optical break-out cable for multimode, 1x MTP (MPO) connector, 8x LC connectors - 5 meters
SFP-FILLER	EMI & dust plug for SFP and SFP+ receptacles
AXP-F-FILL-PANEL	Blank filler panel, AXP1620, AXP1440, AXP1410 – Front
AXP-R-FILL-PANEL	Blank filler panel, AXP1620, AXP1440, AXP1410 – Rear
ACC/CABLE/SER/DTE/6E	MicroDSUB-9 to DSUB-9 serial adapter cable for shelf manager front access ALREADY INCLUDED IN PLATFORM CORE PRODUCTS
CABLE/RJ45/DSUB/6E	RJ45 to DSUB-9 serial adapter and cable for shelf manager rear access
RJ45-DSUB-ATCA	RJ45 to DSUB-9 serial adapter cable for ATCA-F140 serial console

SOLUTION SERVICES

SMART Embedded Computing provides a portfolio of solution services optimized to meet your needs throughout the product lifecycle. Design services help speed time-to-market. Deployment services include worldwide technical support. Renewal services enable product longevity and technology refresh.

CONTACT DETAILS

+1 602-438-5720

Info@smartembedded.com

www.smartembedded.com/ec/contact

The stylized "S" and "SMART", and the stylized "S" combined with "SMART" and "Embedded Computing" are trademarks of SMART Modular Technologies, Inc. Intel, the Intel logo, and Intel Core are trademarks of Intel Corporation in the United States and/or other countries. PICMG, AdvancedTCA, ATCA and the AdvancedTCA logo are trademarks of PICMG. All other trademarks and registered trademarks are the property of their respective companies. ©2019. All rights reserved. For full legal terms and conditions, please visit www.smartembedded.com/ec/legal

AXP1440-Centellis4440-DS 18Dec2019



www.smartembedded.com